


	Smooth
Dimensions:	500mm x 500mm
Thickness:	9.53mm +/- 0.3mm
Weight:	11.24kgs/m ²
Guarantee:	10 Years
Anticipated Service Life:	25 Years +
Material:	PVC
Joint:	Dovetail



		Smooth
Slip Resistance:	EN 14041:2004 DIN 51130:2004	Pass R10
Fire Performance:	BS 476: Part 7 DIN 13501: 2007	Class 1 Spread of Flame Bfl-S1 Does not support combustion
Stain Resistance:	EN 423	Good
Abrasion Wear Resistance:	EN 13845 EN 649	50K Cycles Group T
Mechanical Resistance:	DIN 53516	17N/mm ²
Resistance to Hot Objects/Solder:		Good
Thickness of Wear Layer:	EN 429	6 to 10mm
Hardness:	ISO 868	89-92 Shore A
Impact Resistance:	EN 13329-549	549kg/cm ²
Noise Reduction:	EN 140-8	>46db
Thermal Insulation:		2.62 m ² K/W
Determination of Length, Squareness & Straightness:	BS EN 428:1993	<0.13% / 0.5mm max.
Chemical Resistance:	EN 13529	Good resistance to most commonly used chemicals. Common acid oils & gas oil - No deterioration / Not Resistant to prolonged contact
Colour Fastness:	EN 50105-BO21	5

per ulteriori informazioni contattate:
 FORMAR SRL
 VIA ACHILLE GRANDI 26
 15033 CASALE MONFERRATO (AL)
 ITALIA
 TEL. 0142 455075
 FAX 0142 74834
 WWW.FORMAR.IT