



Altro Wood™ adhesive-free

safety flooring



1000 x 125 mm

Portuguese Oak | AFW280013
WR335 / A1M335 / LRV 51



500/500 x 100 mm

Frosted Oak | AFW280001
WR335 / A1M335 / LRV 52



500/500 x 100 mm

Timeless Oak | AFW280007
WR347 / A1M347 / LRV 38



Altro adhesive-free flooring - swatch shows underside emboss of Altro Wood adhesive-free. Reusable and recyclable post-use.



500/500 x 100 mm

Post Oak | AFW280016
WR350 / A1M483 / LRV 30



500/500 x 100 mm

Champagne Oak | AFW280010
WR338 / A1M338 / LRV 38



500/500 x 100 mm

Summer Oak | AFW280005
WR340 / A1M340 / LRV 37



500/500 x 100 mm

Caramel Oak | AFW280006
WR353 / A1M225 / LRV 25



550/450 x 100 mm

Honey Maple | AFW280011
WR352 / A1M352 / LRV 27



500/500 x 100 mm

Birnam Oak | AFW280017
WR352 / A1M352 / LRV 21



550/450 x 100 mm

Imperial Walnut | AFW280009
WR341 / A1M160 / LRV 15



550/450 x 100 mm

Soft Maple | AFW280002
WR339 / A1M339 / LRV 24



500/500 x 100 mm

Bur Oak | AFW280015
WR514 / A1M514 / LRV 21



550/450 x 100 mm

Shaded Cherry | AFW280004
WR337 / A1M337 / LRV 17



1000 x 125 mm

Oxford Oak | AFW280014
WR339 / A1M339 / LRV 22



550/450 x 100 mm

Holm Oak | AFW280018
WR478 / A1M390 / LRV 26



550/450 x 100 mm

Dusky Cherry | AFW280003
WR336 / A1M239 / LRV 22



1000 x 125 mm

Vintage Oak | AFW280012
WR322 / A1M239 / LRV 19



500/500 x 100 mm

Pitch Oak | AFW280008
WR348 / A1M348 / LRV 7

Dimensions indicate plank size within roll design.



Typical applications

Entrances, corridors, communal areas. Dining, bars. Domestic kitchens. Bedrooms, quiet rooms, libraries. Wards. Classrooms. Shops. Changing areas.

Technical information

	Fire behaviour tested in acc. with	EN ISO 9239-1	≥ 4.5 kW/m ²
	Classified in acc. with	EN ISO 11925-2	Pass
		EN 13501-1	C _f -s1
	Slip resistance	EN 13893	≥ 0.30 / DS
		PTV	≥ 36
		EN 16165 Annex B / ASR A1.5	R10
		EN 13845 Annex C	ESf
	Sound insulation	EN ISO 10140	ca. 14 dB
	Flooring type	EN 651	Safety flooring
	Thickness	EN ISO 24346	2.4 mm
	Wear layer thickness	EN ISO 24340	0.7 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m ²
	Weight	EN ISO 23997	2.4 kg/m ²
	Residual indentation	EN ISO 24343-1	≤ 0.20 mm
	Classification for use	EN ISO 10874	34, 42
	Flexibility	EN ISO 24344	Pass
	Dimensional stability	EN ISO 23999	≤ 0.4 %
	Light fastness	EN ISO 105-BO2	≥ 6
	Castor chair abrasion	ISO 4918	Yes, type W
	Wear resistance	EN 660-2	Group T
	Chemical resistance	EN ISO 26987	Good
	Under floor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	CDPH 1350 / Floorscore Indoor Air Comfort Gold	Approved Approved



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



Sustainability / Nachhaltigkeit / Sostenibilidad



Mitglied der
DGNB
Deutsche Gesellschaft für Nachhaltiges Bauen
German Sustainable Building Council

*A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk

Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance and may affect or invalidate Altro's product guarantee. Technical information on installation and maintenance (including cleaning and staining) can be found at www.altro.com

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.
Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value